

## SCHROEFSTEMPELS, gegalvaniseerd, ABOMA gekeurd



TYPE	B25/N1	B30/N2	B35/N3	B40/N4	B45/N5	B54/N6
AFMETING (mm)	1580-2500	1830-3000	2080-3500	2330-4030	2500-4500	3000-5400
GEWICHT (kg)	14	16	18	19	20	24
HOOGTE (mm)	TOELAATBARE BELASTING KG					
1500						
1600	2780					
1700	2680					
1800	2560	2720				
1900	2440	2670				
2000	2310	2610				
2100	2190	2550	2640			
2200	2090	2480	2540			
2300	1980	2390	2440	2640		
2400	1870	2300	2320	2580		
2500	1750	2200	2240	2500	2010	
2600		2100	2160	2370	1970	
2700		2010	2090	2195	1910	
2800		1890	2010	2040	1860	
2900		1770	1930	1900	1800	
3000		1650	1850	1780	1760	2120
3100			1760	1665	1700	2050
3200			1660	1565	1650	1950
3300			1570	1470	1600	1850
3400			1460	1385	1550	1770
3500			1350	1305	1500	1700
3600				1235	1440	1620
3700				1170	1390	1530
3800				1110	1330	1440
3900				1050	1280	1340
4000				1000	1220	1260
4100					1150	1150
4200					1080	1120
4300					1020	1070
4400					980	1040
4500					940	1020
4600						1000
4700						960
4800						930
4900						900
5000						880
5100						840
5200						810
5300						760
5400						750

## MAMOETSTEMPEL (zware uitvoering met vlakke kopplaat)



TYPE	mammoet	mammoet	mammoet
AFMETING (mm)	2300-4100	0	3100-5500
GEWICHT (kg)	27	30	37
HOOGTE (mm)			
2300	5110		
2400	4850		
2500	4550		
2600	4210		
2700	3980		
2800	3750		
2900	3550		
3000	3360		
3100	3180		4850
3200	3020		4560
3300	2870		4280
3400	2730		4040
3500	2610		3810
3600	2490		3600
3700	2370		3410
3800	2270		3230
3900	2170		3070
4000	2080		2920
4100	1990		2780
4200			2640
4300			2520
4400			2410
4500			2300
4600			2200
4700			2110
4800			2020
4900			1940
5000			1870
5100			1790
5200			1720
5300			1660
5400			1600
5500			1540